



COLOUR MF DIGITAL SYSTEMS

d-Color

P3302

Style and simplicity for the dynamic work group office



- COLOUR
- SPEED
- SILENT
- 7" TOUCHSCREEN
- ECO-FRIENDLY
- WI-FI AND WI-FI DIRECT *

* optional

The world is changing, people change and so do work group environments. Space is now at a premium, and “hot-desking” is becoming more popular as more staff are required to be more flexible and mobile.

Faced with this dynamic situation offices require its printing equipment to keep in step by being compact, silent, functional, efficient, eco-friendly, economic and pleasing to the eye and Olivetti has a printer that achieves all of these qualities!

The Olivetti d-Color P3302 is an A4 colour laser printer which is fast, elegant, productive and simple to use with a new 7" touch-screen providing maximum operational freedom for workgroups on the move.

With environmental sustainability of key importance, low power consumption combined with low noise levels and reduced running costs make the Olivetti d-Color P3302 a printer you cannot do without.



SPEED 33 PAGES PER MINUTE

7" COLOUR TOUCHSCREEN USER INTERFACE

PRINT RESOLUTION UP TO 1200X1200 DPI

COMPACT AND STYLISH

MOBILE PRINTING / WI-FI POSSIBLE AS OPTION

3 GB STANDARD MEMORY PLUS 8 GB MICRO SD



Wide range of connections

Compact and elegant design



TECHNICAL SPECIFICATIONS

3-way paper feed

GENERAL

Type: Desktop, Printer
Technology: A4 Colour Laser
Operator panel: Touch screen, colour, 7 inch
Speed: up to 33 A4 pages per minute, colour and mono
Memory Std/Max: 3 GB (standard/max)
Memory, optional: 8 GB Micro SD
Interfaces: 10/100/1000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n (optional)
Network protocols: TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP
Automatic duplex unit: 60-210 g/m², A5- A4
Input paper capacity (STD/Max): 600 sheets/ 1,100 sheets
Output paper capacity: 250 sheets max.
Standard Paper Drawer: 500 sheets; 60 – 210 g/m²; A6-A4
Paper Drawer (optional): 1 x 500-sheet drawer; 60-90 g/m²; A4
By-pass, manual: 100 sheets; 60 – 210 g/m²; A6-A4;
Automatic feeder, duplex: 60-210 g/m²; A5-A4;
Staple Finisher (optional) off-line (uses SK-501 staples)
Duty cycle (pages/month): Recommended 6,500 pages; Max: 96,000 pages
Warm-up time: Approx. 13 secs for mono; 15 secs for colour
First copy out time: 8.7 secs mono; 9.6 secs colour
Dimensions (WxDxH) base unit: 420x528x473 mm
Base unit weight: 33 kg approx.;
Power consumption: 220 ~ 240 V, 50/60 Hz;
 • Maximum: 986 Watts
 • Copying: 390 Watts
 • Standby: 41 Watts
 • Sleep: 0.5 Watt
TEC: 1.2 kWh/week
Noise levels (Lwad)*: standby 42 dB(A); colour/ mono printing: 65.6/65.3 dB(A)
 *according to ISO7779; RAL-UZ205

Security: ISO15408 Common Criteria (assessment in course); IP Filters and port locking; SSL2; SSL3 and TLS1.0; / 1.1 / 1.2; IEEE 802.1x support; User Authentication; Authentication Register; Secure printing; Kerberos; Automatic deletion of memory data; User data encryption
Accounts: Up to 100 users; Active Directory support (user name + password)
Accounting functions (optional): Biometric authentication; ID card authentication; Authentication via mobile devices

PRINT FUNCTIONS

CPU: Cortex A72 CPU Quad Core 1.6 GHz
Print speeds A4 mono/colour: up to 33 pages per minute
Resolution: Default: 600 x 600 dpi; High definition: 1,200 x 1,200 dpi (lower speed)
Emulation: PCL 6 (XL 3.0); PCL 5c; PostScript 3 (CPSI 3016);
Operating Systems: Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012/R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10; Unix; Linux; Citrix
Printer fonts: 80 PCL Latin, 137 PostScript 3 Latin Emulation
Mobile printing: AirPrint® (iOS); Mobile Print App; NFC Authentication; Google Cloud Print ®(optional); Wi-Fi® Direct (optional)

OPTIONS

Input Media:
PF-P20 (B3762) (B3762) 500-sheet paper drawer (max 2); 60-90 g/m²;
PF-P22 (B3763) Height adjustment unit (max 2)
DK-P04x (B3764) Auxiliary mobile unit

Output Media:
FS-P04 (B3761) Off-line corner stapler, 20-sheet

Connectivity:

EK-P10 (B3768) NFC Interface
EK-P08 (B3765) USB keypad connector
EK-P09 (B3766) USB keypad connector; Bluetooth
UK-221 (B3755) Wireless LAN and wireless LAN Access Point mode
SX-BR-300AN-WIRELESS LAN (B3855) Wireless LAN network card
AU-102 (B5359) Biometric authentication. Vein pattern reader
ID CARD READER Various technologies
MK-P08 (B3769) ID card reader Installation Kit

Others:

WT-P03 (B3759) Work table
KP-103 (B3833) 10-number keypad
KH-P02 (B3834) USB keypad support shelf
MK-P09 (B3771) CU-202 Installation Kit
CU-202 (B3423) Air cleaning unit; improves quality of ambient air through emission reduction

CONSUMABLES

Black toner (B1345) yield up to 13,000 pages (5% coverage)
Cyan toner (B1344) yield up to 9,000 pages (5% coverage)
Magenta Toner (B1346) yield up to 9,000 pages (5% coverage)
Yellow Toner (B1347) yield up to 9,000 (5% coverage)
Black Image Unit (B1349) yield up to 154K pages
Cyan Image Unit (B1348) yield up to 55K pages
Magenta Image Unit (B1350) yield up to 55K pages
Yellow Image Unit (B1351) yield up to 55K pages
Transfer Roller (B1375) Life up to 154K
Transfer Belt Unit (B1374) Life up to 154K
Fuser Unit (B1373) Life up to 400K
Waste Toner Unit (B1356) Box capacity approx. 36,000 for mono; 9,000 for colour
SK-501 (B1113) staples, 5 cartridges x 1,000 staples

- All specifications related to paper capacities refer to A4 sheets of weight 80 g/m².
- Availability of specifications and functionalities outlined here depend on operating systems, applications, and network protocols, as well as network and system configurations.
- The expected lifetime of each consumable depends on the specific operating conditions, such as page coverage in the case of particular page formats (5% coverage). The actual lifetime of each consumable varies according to page coverage, format, media type, continuous or intermittent printing frequency, temperature and humidity.
- In certain illustrations, the product is shown with optionally available accessories.
- Specifications and accessories are based on information available at the time of printing and are subject to modification without notice.
- Olivetti offers no guarantee that the specifications given here are free from errors. E&OE